

# SafetyLink TileLink™

## Rafter-Mounted Anchor

Quick to install, with amazing performance ability SafetyLink's patented TileLink™ is the perfect anchor for tile and slate roofs.

Its combines energy absorbing capabilities with a design that is practically invisible when looking at the roof.

**ADJUSTS TO SUIT TILE PATTERN**



**NEW**



**SafetyLink Pty Ltd**

PO Box 88 | HAWKS NEST NSW 2324 | Australia  
Phone: 1300 789 545 or 02 4997 2272 | Fax: 1300 738 071

[safetylink@heightsafety.com.au](mailto:safetylink@heightsafety.com.au)

[www.heightsafety.com](http://www.heightsafety.com)



# SafetyLink TileLink™

## Rafter-Mounted Anchor

**PRODUCT CODE: TILEL001**

### TileLink Complete Unit

Quick to install, with amazing performance ability SafetyLink's patented TileLink™ is the perfect anchor for tile and slate roofs.

It combines energy absorbing capabilities with a design that is practically invisible when looking at the roof.

The TileLink's design emulates the extraordinary FrogLink™ energy absorbing regions allowing it in the event of a fall to reduce the impact on the structure and person attached to the TileLink™.



Its sleek design means fixing to a rafter is a simple task of screwing five roofing screws (12 gauge, 50mm long) through the existing holes. Five alternate fixing rows enable the TileLink™ to be positioned to suit the pattern of the roof tile. Because the TileLink™ fits snugly between the existing tile pattern there is no waterproofing issues to worry about.

The stainless steel TileLink™ is tested and manufactured in accordance with the applicable Australian and New Zealand Standards AS/NZS 1891.4 and is rated as a two person anchor.



Distributors of SafetyLink Pty Ltd Products  
[www.heightsafety.com](http://www.heightsafety.com)

